

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

**INFORMAL PROPOSED CLAIMS FOR TELEPHONIC INTERVIEW**

A. (proposed) A product pasteurizing section for a beverage container filling plant for filling beverage containers such as bottles or containers with a beverage, said product pasteurizing section being configured to permit at least heating and cooling of the content in containers, said product pasteurizing section comprising:

20326

a housing comprising a roof arrangement, an inlet arrangement configured to receive containers into said housing, and an outlet arrangement configured to discharge containers from said housing;

6

a plurality of spray arrangements being disposed within said roof arrangement;

each of said plurality of spray arrangements comprising a spray nozzle being configured to spray a stream of liquid;

each of said spray nozzles being disposed integrally within said roof arrangement;

said plurality of spray arrangements and said roof arrangement being configured to be disposed above the containers to permit spraying of containers from above the containers;

said plurality of spray arrangements in said roof arrangement comprising:

a first roof portion of spray arrangements;

said first roof portion being configured:

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

to receive containers from said inlet arrangement;

and

to be disposed to heat the beverage in containers  
with a first, heated, spray of liquid having a predetermined  
first temperature to bring the beverage in containers to a  
temperature below the pasteurization temperature of the  
beverage;

a second roof portion of spray arrangements;

said second roof portion being configured to pasteurize the  
beverage in containers with a second, heated, spray of liquid  
having a predetermined second temperature to bring the  
beverage in containers to the pasteurization temperature of the  
beverage; and

a third roof portion of spray arrangements;

said third roof portion being configured to cool the  
beverage in containers with a third spray of liquid having a  
predetermined third temperature to bring the beverage in  
containers to a temperature below said second temperature;

said second roof portion being configured:

to be disposed adjacent to said first roof portion;

and

to receive containers from said first roof portion; and

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

said third roof portion being configured:

to be disposed adjacent to said second roof portion;

to receive containers from said second roof portion;

and

to discharge containers through said outlet

arrangement from said housing.

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

B. (proposed) A product pasteurizing section for a beverage container filling plant for filling beverage containers such as bottles or containers with a beverage, said product pasteurizing section being configured to permit at least heating and cooling of the content in containers, said product pasteurizing section comprising:

a housing comprising a roof arrangement, an inlet arrangement configured to receive containers into said housing, and an outlet arrangement configured to discharge containers from said housing;

a plurality of spray arrangements being disposed within said roof arrangement;

each of said plurality of spray arrangements comprising a spray nozzle being configured to spray a stream of liquid;

said roof arrangement comprising an outer, upper, roof surface and an inner, lower, roof surface disposed opposite and below said inner, upper, roof surface;

each of said spray nozzles being disposed on said second, lower, roof surface;

said plurality of spray arrangements and said roof arrangement being configured to be disposed above the containers to permit spraying of containers from above the containers;

said plurality of spray arrangements in said roof arrangement comprising:

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

a first roof portion of spray arrangements;

said first roof portion being configured:

to receive containers from said inlet arrangement;

and

to be disposed to heat the beverage in containers  
with a first, heated, spray of liquid having a predetermined  
first temperature to bring the beverage in containers to a  
temperature below the pasteurization temperature of the  
beverage;

a second roof portion of spray arrangements;

said second roof portion being configured to pasteurize the  
beverage in containers with a second, heated, spray of liquid  
having a predetermined second temperature to bring the  
beverage in containers to the pasteurization temperature of the  
beverage; and

a third roof portion of spray arrangements;

said third roof portion being configured to cool the  
beverage in containers with a third spray of liquid having a  
predetermined third temperature to bring the beverage in  
containers to a temperature below said second temperature;

said second roof portion being configured:

to be disposed adjacent to said first roof portion;

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

and

to receive containers from said first roof portion; and  
said third roof portion being configured:

to be disposed adjacent to said second roof portion;

to receive containers from said second roof portion;

and

to discharge containers through said outlet  
arrangement from said housing.

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

C. (proposed) A product pasteurizing section for a beverage container filling plant for filling beverage containers such as bottles or containers with a beverage, said product pasteurizing section being configured to permit at least heating and cooling of the content in containers, said product pasteurizing section comprising:

a housing comprising a roof arrangement, an inlet arrangement configured to receive containers into said housing, and an outlet arrangement configured to discharge containers from said housing;

a plurality of spray arrangements being disposed within said roof arrangement;

each of said plurality of spray arrangements comprising a spray nozzle being configured to spray a stream of liquid;

said roof arrangement comprising an outer, upper, roof surface and an inner, lower, roof surface disposed opposite and below said inner, upper, roof surface;

each of said spray nozzles being disposed immediately adjacent said second, lower, roof surface;

said plurality of spray arrangements and said roof arrangement being configured to be disposed above the containers to permit spraying of containers from above the containers;

said plurality of spray arrangements in said roof arrangement comprising:

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

a first roof portion of spray arrangements;

said first roof portion being configured:

to receive containers from said inlet arrangement;

and

to be disposed to heat the beverage in containers

with a first, heated, spray of liquid having a predetermined

first temperature to bring the beverage in containers to a

temperature below the pasteurization temperature of the

beverage;

a second roof portion of spray arrangements;

said second roof portion being configured to pasteurize the

beverage in containers with a second, heated, spray of liquid

having a predetermined second temperature to bring the

beverage in containers to the pasteurization temperature of the

beverage; and

a third roof portion of spray arrangements;

said third roof portion being configured to cool the

beverage in containers with a third spray of liquid having a

predetermined third temperature to bring the beverage in

containers to a temperature below said second temperature;

said second roof portion being configured:

to be disposed adjacent to said first roof portion;



Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

and

to receive containers from said first roof portion; and  
said third roof portion being configured:

to be disposed adjacent to said second roof portion;

to receive containers from said second roof portion;

and

to discharge containers through said outlet  
arrangement from said housing.

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

D. (proposed) A product pasteurizing section for a beverage container filling plant for filling beverage containers such as bottles or containers with a beverage, said product pasteurizing section being configured to permit at least heating and cooling of the content in containers, said product pasteurizing section comprising:

a housing comprising a roof arrangement, an inlet arrangement configured to receive containers into said housing, and an outlet arrangement configured to discharge containers from said housing;

a plurality of spray arrangements being disposed within said roof arrangement;

each of said plurality of spray arrangements comprising a spray nozzle being configured to spray a stream of liquid;

said roof arrangement comprising an outer, upper, roof surface and an inner, lower, roof surface disposed opposite and below said inner, upper, roof surface;

each of said spray nozzles being disposed in contact with said second, lower, roof surface;

said plurality of spray arrangements and said roof arrangement being configured to be disposed above the containers to permit spraying of containers from above the containers;

said plurality of spray arrangements in said roof arrangement comprising:

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

a first roof portion of spray arrangements;

said first roof portion being configured:

to receive containers from said inlet arrangement;

and

to be disposed to heat the beverage in containers  
with a first, heated, spray of liquid having a predetermined  
first temperature to bring the beverage in containers to a  
temperature below the pasteurization temperature of the  
beverage;

a second roof portion of spray arrangements;

said second roof portion being configured to pasteurize the  
beverage in containers with a second, heated, spray of liquid  
having a predetermined second temperature to bring the  
beverage in containers to the pasteurization temperature of the  
beverage; and

a third roof portion of spray arrangements;

said third roof portion being configured to cool the  
beverage in containers with a third spray of liquid having a  
predetermined third temperature to bring the beverage in  
containers to a temperature below said second temperature;

said second roof portion being configured:

to be disposed adjacent to said first roof portion;

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

and

to receive containers from said first roof portion; and  
said third roof portion being configured:

to be disposed adjacent to said second roof portion;

to receive containers from said second roof portion;

and

to discharge containers through said outlet  
arrangement from said housing.

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

E. (proposed) A product pasteurizing section for a beverage container filling plant for filling beverage containers such as bottles or containers with a beverage, said product pasteurizing section being configured to permit at least heating and cooling of the content in containers, said product pasteurizing section comprising:

a housing comprising a roof arrangement, an inlet arrangement configured to receive containers into said housing, and an outlet arrangement configured to discharge containers from said housing;

a plurality of spray arrangements being disposed within said roof arrangement;

each of said plurality of spray arrangements comprising a spray nozzle being configured to spray a stream of liquid;

said roof arrangement comprising an outer, upper, roof surface and an inner, lower, roof surface disposed opposite and below said inner, upper, roof surface;

each of said spray nozzles being disposed on, immediately adjacent, and in contact with said second, lower, roof surface;

said plurality of spray arrangements and said roof arrangement being configured to be disposed above the containers to permit spraying of containers from above the containers;

said plurality of spray arrangements in said roof arrangement comprising:

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

a first roof portion of spray arrangements;

said first roof portion being configured:

to receive containers from said inlet arrangement;

and

to be disposed to heat the beverage in containers  
with a first, heated, spray of liquid having a predetermined  
first temperature to bring the beverage in containers to a  
temperature below the pasteurization temperature of the  
beverage;

a second roof portion of spray arrangements;

said second roof portion being configured to pasteurize the  
beverage in containers with a second, heated, spray of liquid  
having a predetermined second temperature to bring the  
beverage in containers to the pasteurization temperature of the  
beverage; and

a third roof portion of spray arrangements;

said third roof portion being configured to cool the  
beverage in containers with a third spray of liquid having a  
predetermined third temperature to bring the beverage in  
containers to a temperature below said second temperature;

said second roof portion being configured:

to be disposed adjacent to said first roof portion;

Examiner Eugene Kim  
Examiner Sameh Tawfik  
Art Unit: 3721

Docket No.: NHL-HOL-55  
Serial No.: 09/942,254  
Fax No.: 703-872-9306

and

to receive containers from said first roof portion; and  
said third roof portion being configured:

to be disposed adjacent to said second roof portion;

to receive containers from said second roof portion;

and

to discharge containers through said outlet  
arrangement from said housing.